136.

Accession number:20113414251260

Title:Dual-wavelength, two-crystal, continuous-wave optical parametric oscillator

Authors:Samanta, G.K. (1); Ebrahim-Zadeh, M. (1)

Author affiliation:(1) ICFO-Institut de Ciencies Fotoniques, Mediterranean Technology Park, 08860 Castelldefels, Barcelona, Spain; (2) Physical Research Laboratory, Navarangpura, Ahmedabad 380 009, India; (3) Institucio Catalana de Recerca i Estudis Avancats (ICREA), Passeig Lluis Companys 23, Barcelona 08010, Spain

Corresponding author:Samanta, G.K.(gsamanta@prl.res.in)

Source title:Optics Letters

Abbreviated source title:Opt. Lett.

Volume:36

Issue:16

Issue date:August 15, 2011

Publication year:2011

Pages:3033-3035

Language:English

ISSN:01469592

E-ISSN:15394794

CODEN:OPLEDP

Document type:Journal article (JA)

Publisher:Optical Society of America, 2010 Massachusetts Avenue NW, Washington, DC 20036-1023, United States

Abstract: We report a cw optical parametric oscillator (OPO) in a novel architecture comprising two nonlinear crystals in a single cavity, providing two independently tunable pairs of signal and idler wavelengths. Based on a singly resonant oscillator design, the device permits access to arbitrary signal and idler wavelength combinations within the parametric gain bandwidth and reflectivity of the OPO cavity mirrors. Using two identical 30 mm long MgO:sPPLT crystals in a compact four-mirror ring resonator pumped at 532 nm, we generate two pairs of signal and idler wavelengths with arbitrary tuning across 850–1430 nm, and demonstrate a frequency separation in the resonant signal waves down to 0.55 THz. Moreover, near wavelength-matched condition, coherent energy coupling between the resonant signal waves, results in reduced operation threshold and increased output power. A total output power >2.8 W with peak-to-peak power stability of 16% over 2 h is obtained.