368

Accession number:20114714552057

Title:Matrix structure of metamaterial absorbers for multispectral terahertz imaging

Authors:Kuznetsov, S.A. (1); Paulish, A.G. (1); Gelfand, A.V. (3); Lazorskiy, P.A. (3); Fedorinin, V.N. (3)

Author affiliation:(1) Novosibirsk State University, Pirogova St., 2, Novosibirsk 630090, Russia; (2) Budker Institute of Nuclear Physics SB RAS National Institute, Lavrentiev Ave, Novosibirsk 630090, Russia; (3) Institute of Semiconductor Physics SB RAS, Novosibirsk Branch 'TDIAM', Lavrentiev Ave., 2/1, Novosibirsk 630090, Russia

Corresponding author: Paulish, A. G. (paulish63@ngs.ru)

Source title:Progress in Electromagnetics Research

Abbreviated source title:Prog. Electromagn. Res.

Volume:122

Issue date:2011

Publication year:2011

Pages:93-103

Language:English

ISSN:10704698

E-ISSN:15598985

Document type:Journal article (JA)

Publisher:Electromagnetics Academy, 77 Massachusetts Avenue, Room 26-305, Cambridge, MA 02139, United States

Abstract:A multispectral 24×24 bolometric matrix structure of terahertz (THz) absorbers operating at 0.3-0.4 THz was proposed and experimentally investigated. Each pixel of the structure was implemented as a fragment of an ultra-thin metamaterial absorber. The matrix structure consisted of four types of pixels with nearly perfect absorptivity. Three pixels were at 0.30, 0.33, 0.36 THz respectively with identically oriented polarization sensitivity, and the fourth pixel was at 0.33 THz oriented with polarization sensitivity orthogonal to foregoing ones. The backside of the structure included a high-performance infrared emissive layer. Resonant absorption of THz radiation induced the structure heating and increasing IR emission from the emissive layer, which was henceforth detected by the IR camera. The terahertz imaging system, capable to operate in real time, with spectral and polarization resolution together with acceptable spatial resolution.

Number of references:31