

Accession number:20114014405027

Title:Measurement stand for TeraEYE inspection

Authors:Piszczyk, M. (1); Kowalski, M. (1); Szustakowski, M. (1)

Author affiliation:(1) Institute of Optoelectronic, Military University of Technology, S. Kaliskiego 2, 00-908 Warsaw, Poland

Corresponding author:Piszczyk, M.(mpiszczyk@wat.edu.pl)

Source title:Acta Physica Polonica A

Abbreviated source title:Acta Phys Pol A

Volume:120

Issue:4

Monograph title:Optical and Acoustical Methods in Science and Technology

Issue date:October 2011

Publication year:2011

Pages:720-724

Language:English

ISSN:05874246

E-ISSN:1898794X

CODEN:ATPLB6

Document type:Journal article (JA)

Publisher:Polish Academy of Sciences, Al. Lotnikow 32-46, Warszawa, 02-668, Poland

Abstract:Image fusion can be used as one of imaging methods. Connection of images acquired using different acquisition methods can deliver information invisible for traditional one imaging technique. Visible and thermal images connected in one image give information about shapes and temperature map of objects seen by cameras. If we connect stereoscopic visible image and thermal image we will have three-dimensional object model covered with temperature map. Dividing three-dimensional objects on elementary surfaces we can model this object energetically. Energetic modeling of measurement scene allows verifying measurement data acquired from devices working in terahertz frequency range. This method requires many measurement scene parameters to be registered. Some of these parameters can be used in a hybrid modelling process.

Number of references:8