

404.

Accession number:12996519

Title:Low-power inelastic light scattering at small detunings in silicon wire waveguides at telecom wavelengths

Authors:Clemmen, S. (1); Perret, A. (2); Safioui, J. (3); Bogaerts, W. (4); Baets, R. (4); Gorza, S.-P. (3); Emplit, P. (3); Massar, S. (1)

Author affiliation:(1) Lab. d'Inf. Quantique, Univ. Libre de Bruxelles (U. L. B.), Brussels, Belgium; (2) Dept. de Phys., Ecole Normale Super., Paris, France; (3) Service OPERA-Photonique, Univ. Libre de Bruxelles (U. L. B.), Brussels, Belgium; (4) INTEC-Dept., Ghent Univ. - IMEC, Ghent, Belgium

Source title:Journal of the Optical Society of America B (Optical Physics)

Abbreviated source title:J. Opt. Soc. Am. B, Opt. Phys. (USA)

Volume:29

Issue:8

Publication date:Aug. 2012

Pages:1977-82

Language:English

ISSN:0740-3224

CODEN:JOBPDE

Document type:Journal article (JA)

Publisher:Optical Society of America

Country of publication:USA

Material Identity Number:CN50-2012-004

Abstract:When a pump beam is propagating through a silicon nanophotonic waveguide, a very small fraction of the light is scattered to other frequencies. At very low intensity, the amount of scattered light is proportional to the power of the pump beam. We show that the scattering intensity increases linearly within the temperature range 300-575 K and that the photon flux decreases as the inverse of the frequency detuning over the investigated bandwidth 0.4 THz to 2.5 THz. The simplest interpretation of these observations is that the pump beam is scattered on a one-dimensional thermal bath of excitations. Finally, the implications of this scattering process for quantum optics applications of silicon nanophotonic structures are discussed.

Number of references:23

Inspec controlled terms:elemental semiconductors - light propagation - light scattering - nanophotonics - nanowires - optical pumping - optical tuning - optical waveguides - quantum optics - silicon

Uncontrolled terms:low-power inelastic light scattering - silicon wire waveguides - telecom wavelengths - pump beam - silicon nanophotonic waveguide - scattering intensity - photon flux - frequency detuning - one-dimensional thermal bath - quantum optics applications - silicon nanophotonic structures - temperature 300 K to 575 K - Si

Inspec classification codes:A4280L Optical waveguides and couplers - A4284 - A4250 Quantum optics - B4130 Optical waveguides - B4146

Numerical data indexing:temperature 3.0E+02 5.75E+02 K

Chemical indexing:Si/el

Treatment:Experimental (EXP)

Discipline:Physics (A); Electrical/Electronic engineering (B)

DOI:10.1364/JOSAB.29.001977

Database:Inspec

IPC Code:B82B1/00; G02B6/10; H01S3/091Copyright 2012, The Institution of Engineering and Technology